

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
1 September 2005 (01.09.2005)

PCT

(10) International Publication Number
WO 2005/081009 A1

(51) International Patent Classification⁷: **G01R 33/38**,
H01F 6/04

(21) International Application Number:
PCT/GB2005/050013

(22) International Filing Date: 14 February 2005 (14.02.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0403113.4 12 February 2004 (12.02.2004) GB

(71) Applicant (for all designated States except US): **MAGNEX SCIENTIFIC LIMITED** [GB/GB]; The Magnet Technology Centre, 6 Mead Road, Oxford Industrial Park, Yarnton, Oxford Oxfordshire OX5 1QU (GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **BURGESS, Stephen** [GB/GB]; 8 Green Lane, Bayworth, Abingdon, Oxfordshire OX13 6RG (GB). **VARNEY, Andrew, John** [GB/GB]; 24 Merton Way, Yarnton, Kidlington, Oxford, Oxfordshire OX5 1NN (GB). **HOULDEN, Darren** [GB/GB]; 17 Winterborne Road, Abingdon, Oxfordshire OX14 1AJ (GB).

(74) Agent: **HARDING, Richard**; Marks & Clerk, 4220 Nash Court, Oxford Business Park South, Oxford, Oxfordshire OX4 2RU (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

[Continued on next page]

(54) Title: CRYOGENIC COOLING OF SUPERCONDUCTING MAGNET SYSTEMS BELOW TEMPERATURE OF 4 . 2 K



(57) Abstract: A superconducting magnet system comprises a cryogenic vessel (1), a superconducting magnet (11) contained in an inner reservoir (16) within the vessel (1) to be cooled by liquid helium within the inner reservoir (16), and an outer reservoir (7) containing liquid helium and linked to the inner reservoir (16) by a feed tube (10) and a needle valve (9). In operation of the system current is supplied to the magnet (11) by a removable current lead (19) extending through the wall of the vessel (1) by way of a supply passage (17) in order to initiate superconducting current flow in the magnet. The supply of current to the magnet (11) is then stopped and the lead (19) is removed whilst the superconducting current flow persists in the magnet. After an extended period of superconducting current flow in the magnet (11) and without stopping such superconducting current flow, liquid helium at a temperature of about 4.2 K may be supplied to an upper part of the inner reservoir (16) above the magnet (11) from the outer reservoir (7) such that the magnet is still surrounded by liquid helium at a temperature of below 4.2 K. After a period of time the supply of liquid helium to the inner reservoir 16 is stopped, and the liquid helium in the inner reservoir (7) is cooled to a temperature below 4.2 K. Such a system is capable of being operated at very low temperatures down to below the lambda point, and of producing magnetic fields of high strengths and stability suitable for NMR spectroscopy.



WO 2005/081009 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.